


IP Kontakt Pl. Zwycięstwa 2E 90-312 Łódź

Polska e-mail: ipkontakt@ipkontakt.pl

tel. +48 42 676 75 25

+48 42 674 22 74 fax: +48 42 676 49 25

H-NTSS - Stalowe opaski kablowe





Details:

- Material: AISI 304 or 316 stainless steel with PVC coating
- For ease of assembly, position locking head so the widest end is down.
- Stainless steel cable ties have more strength and better durability than nylon cable ties.
- Locking ball design for maximum holding strength and ease of installation.
- Coated ties offer additional protection and separation of dissimilar metals for improved corrosion resistance.
- Suitable for harsh outdoor environments; conform to standard IEC92 for Marine Electrical Appliances and the requirements of CB1113-85 "Plastic Covered Metal Cable Ties", "Steel Sea Boats Construction Level Standard."
- Secure bundles in moist and high temperature environments with decay, fire, corrosion, and radio resistance.
- $\bullet\,$ Widely used in shipping, communication, and flight applications.
- .010" (0,25 mm) thick.
- Custom lengths available on special order.
- Standard pack: 100 pcs

Part No.	Tensile strength	Max. bundle diameter	А	В	Stainless steel	Coating
	[N]	[mm]			Steel	
H-12884	1115	240.0	800	7.9	AISI 316	no

ipkontakt.pl Page 1 of 1