

DTS-ZK2 - Double sided adhesive tape



Details:

- Black PE-Foam coated on both sides with a solvent acrylic adhesive
- Strong adhesion and superb holding power.
- It has strong holding power on various surfaces, e.g. PVC, ABS, PC, steel, aluminium, et
- It has very good durability, which is resistant to moisture, UV and temperature changes.
- The foam material act as a gentle shock absorbent.
- Applications: Mounting and bonding of various substrates, such as: Small ornamental displays, bathroom mirrors, automobile emblems and nameplates.
- The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product.
- STORAGE & SHELF LIFE Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year.
- APPLICATION Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

Part No	Adhesive	Carrier	Thickness	Liner	FINAT 1	Temperature
			[mm]		[N/25mm]	[°C]
DTS-ZK2-875	Modified Solvent Acrylic	Black PE-Foam 200 kg/m ³	0,8	White PE coated paper	≥20	-20 - +80 (long term), -40 - +150 (short term)