

IP Kontakt Pl. Zwycięstwa 2E 90-312 Łódź

Polska

e-mail: ipkontakt@ipkontakt.pl


tel. +48 42 676 75 25

fax: +48 42 676 49 25

+48 42 674 22 74

DTS-430 - Double-Sided Adhesive Tape with Tissue Carrier





Details:

- DTS-430 is a double sided adhesive tape with a special tissue carrier and modified acrylic adhesive.
- This tape is a good ,all rounder' for mainly interior use.
- It has well balanced adhesive properties, a good resistance to ageing and UV light, and can withstand extremes of temperature.
- Its high tack gives an excellent adhesion to practically any material
- DTS-430 is preferably used for:
 - o mounting name-plates and decorative profiles
 - o lamination of foams (polyester, polyether, PVC, polyethylene)
 - $\circ\,$ laminating felt, film, cloth and paper
 - $\circ\,$ fixing displays and advertising material
 - film and paper splicing
- Shear Adhesion (25 mm² on V2A steel, 1 kg weight at 23° and 50 % rel. atmospheric humidity): >10 h
- The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product
- Storage: Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year
- Application: Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

Part No.	Adhesive	Carrier	Thickness	Liner	Peel 180°	Temperature	
						from	to
			[mm]		[N/25mm]	[°C]	
DTS-430	Akrylowy	Bibuła, czarna	0,10	Papier, miodowy	> 25	-20°C	120°C

ipkontakt.pl Page 1 of 1