

IP Kontakt Pl. Zwycięstwa 2E 90-312 Łódź

Polska e-mail: ipkontakt@ipkontakt.pl

tel. +48 42 676 75 25

fax: +48 42 676 49 25

+48 42 674 22 74

## DTS-ATG - Transfer Tapes without Carrier



## Details:

- DTS-ATG is a general purpose transfer tape with good adhesion to most paperstocks. It is ideal for folders, photo mounting, splicing paper, foils and films.
- Adhesive Solvent Acrylic with Glass Fibres
- Liner: Honey Silicone Paper
- The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product
- Storage: Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year
- Application: Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

Part No.	Width	Thickness	Length	Siła odrywania (PSTC 1)	llość rolek / karton	Temperatura
	[mm]		[m]	[+/- 0,5 N / 25 mm]	[pcs]	[°C]
DTS-ATG-306-09	9	0.05	33	15	96	-30 do + 180

ipkontakt.pl Page 1 of 1