

## DTS-ATG - Transfer Tapes without Carrier



### Details:

- DTS-ATG is a general purpose transfer tape with good adhesion to most paperstocks. It is ideal for folders, photo mounting, splicing paper, foils and films.
- Adhesive Solvent Acrylic with Glass Fibres
- Liner: Honey Silicone Paper
- The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product
- Storage: Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year
- Application: Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

| Part No.       | Width | Thickness | Length | Siła odrywania<br>(PSTC 1)             | Ilość rolek<br>/ karton | Temperatura  |
|----------------|-------|-----------|--------|----------------------------------------|-------------------------|--------------|
|                | [mm]  |           | [m]    | [+/- 0,5 N / 25 mm]                    | [pcs]                   | [°C]         |
| DTS-ATG-318-12 | 12    | 0.03      | 50     | strona otwarta: 7; strona zamknięta: 2 | 72                      | -30 do + 150 |