

IP Kontakt Pl. Zwycięstwa 2E 90-312 Łódź

+48 42 674 22 74 fax: +48 42 676 49 25

tel. +48 42 676 75 25

Polska e-mail: ipkontakt@ipkontakt.pl

## DTS-T-446 - Double-Sided Adhesive Tapes with Cloth Carrier



## Details:

- DTS-446 is high-quality double-sided cloth installation tape for professional requirements.
- The covered side of the tape is coated with a permanent acrylic adhesive, while the removable adhesive on the open side can be removed from almost a ll surfaces without leaving any residue
- DTS-446 is solvent-free and has a good resistance to aging and plasticizers
- Shear Adhesion (25 mm² on V2A steel, 1 kg weight at 23° and 50 % rel. atmospheric humidity): >1 h
- The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product
- Storage: Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year
- Application: Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

Part No.	Material samoprzylepny	Nośnik	Thickness	Przekładka	Odrywanie 180°	Temperature	
						from	to
			[mm]		[N/25mm]	[°C]	
DTS-T-446-R	Acrylic, removable	fabric	0,32	Paper, white	> 3	-20	100

ipkontakt.pl Page 1 of 1