


DTS-S-375 - Double-Sided Adhesive Tapes with Scrim Carrier



Details:

- This very addressive mounting tape is a stronger variant of the DTS-370 with double the coat weight of adhesive.
- It is characterised by its extremely high initial tack and very strong permanent adhesion.
- **DTS-375** is ideally suitable for fixing hard skirting boards and all other skirting to rough, uneven and difficult surfaces.
- The tapes extra high adhesive coating weight counteracts any unevenness in the surface of the substrate.
- Shear Adhesion (25 mm² on V2A steel, 1 kg weight at 23° and 50 % rel. atmospheric humidity): >1 h
- The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product

Storage: Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year

- Application: Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

Part No.	Material samoprzylepny	Nośnik	Thickness	Przekładka	Odrywanie 180°	Temperatura	
			[mm]			od	do
					[N/25mm]	[°C]	
DTS-S-375	Acrylic	gaza	0.42	Paper, white	> 30	-40	100