

IP Kontakt Pl. Zwycięstwa 2E 90-312 Łódź

Polska

fax: +48 42 676 49 25 e-mail: ipkontakt@ipkontakt.pl

tel. +48 42 676 75 25

+48 42 674 22 74

DTS-FHR-465 - Peel Resistant Double Sided Adhesive Tape



Details:

- DTS-465 is an assembling system consisting of a thin PET film carrier coated on both sides with a solvent based acrylic adhesive.
- It offers a very high initial tack, superior adhesion and outstanding holding power.
- The tape has good die-cutting properties and excellent resistance against environmental influence, e.g. light, heat and humidity.
- DTS-465 offers an excellent immediate adhesion and reliable bonding to smooth, rough or low-engergy surfaches, e.g. PP, PE, etc.
- Widely used in digital electronic industries, e.g. mounting of screen / battery compartment / rubber parts or assembly of framework in mobile phone and digital camera industries.
- The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product
- Storage: Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year
- Application: Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease.
 Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

| Part No. | Adhesive | Backing | Thickness | Coverage | Adhesive strength 180° | Temperatura | |
|-------------|--------------------|-----------------------|-----------|-----------|------------------------|-------------|-----|
| | | | | | | od | do |
| | | | [mm] | | [N/25mm] | [°C] | |
| DTS-FHR-465 | Solvent - Acrylate | PET foil, transparent | 0.2 | MOPP, red | >20 | -40 | 180 |

ipkontakt.pl Page 1 of 1