

DTS-FHR-465 - Peel Resistant Double Sided Adhesive Tape



Details:

- DTS-465 is an assembling system consisting of a thin PET film carrier coated on both sides with a solvent based acrylic adhesive.
- It offers a very high initial tack, superior adhesion and outstanding holding power.
- The tape has good die-cutting properties and excellent resistance against environmental influence, e.g. light, heat and humidity.
- DTS-465 offers an excellent immediate adhesion and reliable bonding to smooth, rough or low-energy surfaces, e.g. PP, PE, etc.
- Widely used in digital electronic industries, e.g. mounting of screen / battery compartment / rubber parts or assembly of framework in mobile phone and digital camera industries.
- The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product
- Storage: Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year
- Application: Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

Part No.	Adhesive	Backing	Thickness	Coverage	Adhesive strength 180°	Temperatura	
			[mm]			od	do
					[N/25mm]	[°C]	
DTS-FHR-465	Solvent - Acrylate	PET foil, transparent	0.2	MOPP, red	>20	-40	180