

IP Kontakt Pl. Zwycięstwa 2E 90-312 Łódź

Polska

fax: +48 42 676 49 25 e-mail: ipkontakt@ipkontakt.pl

tel. +48 42 676 75 25

+48 42 674 22 74

DTS-FUV-460 - Double Sided Adhesive Tape, UV Resistant



Details:

- DTS-460 is a double sided adhesive tape with PET carrier and modified acrylic adhesive. It has good adhesive properties and UV-resistance and is suitable for mounting displays, profiles etc.
- Shear Adhesion (25 mm² on V2A steel, 1 kg weight at 23° and 50 % rel. atmospheric humidity): >10 h
- The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product
- Storage: Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year
- Application: Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

Part No.	Adhesive	Backing	Thickness	Coverage	Adhesive strength 180°	Temperatura	
						od	do
			[mm]		[N/25mm]	[°C]	
DTS-FUV-460	Acrylate	PET foil, transparent	0.12	Silicon paper, yellow-brown	>25	-20	100

ipkontakt.pl Page 1 of 1