

## CTS-SUV - Screw Mount Cable Tie, UV Resistant



### Details:

- **Polyamid 6.6, UL 94 V-2 (V-0 na żądanie)**
- **Color:** BLK - black
- UV Resistant
- Cable ties with crew mounting hole
- Working temperature: -35°C do +85°C
- Complies with: E 75050 (S) Spec.: UL appr.; Mil.Spec. 23190D
- Standard pack: 100 pcs

Symbol	Length L	Width B	Max. cable bundle diameter	Breaking force	Mounting hole diameter	Material	Flammability	Color
	[mm]	[mm]	[mm]	[daN]	[mm]			
CTS-S-11025-H-UV	110	2.5	22	8.1	3.2	PA 66	UL94 V-2	black
CTS-S-15036-H-UV	150	3.6	32	18.2	4.2	PA 66	UL94 V-2	black
CTS-S-20048-H-UV	200	4.8	50	22.2	5.5	PA 66	UL94 V-2	black
CTS-S-20076-H-UV	200	7.6	50	54.4	5.7	PA 66	UL94 V-2	black
CTS-S-30076-H-UV	313	7.6	76	54.4	5.7	PA 66	UL94 V-2	black
CTS-S-37076-H-UV	382	7.6	98	54.4	6.3	PA 66	UL94 V-2	black