

CTS-T - High Temperature Resistant Cable Tie



Details:

- **Polyamid 6.6 heat stabilized**
- **Color:** NAT - natural (light green)
- Working temperature: -35°C do +110°C
- Short term working temperature: up to +145°C
- Complies with: E 75050 (S) Spec.: UL appr.; Mil.Spec. 23190D
- Standard pack: 100 pcs

Symbol	Length L	Width B	Max. cable bundle diameter	Breaking force	Material	Flammability	Color
	[mm]	[mm]	[mm]	[daN]			
CTS-T-CV-10025	100	2.5	20	8	PA 66	UL94 V-2	natural
CTS-T-CV-12025	120	2.5	25	8	PA 66	UL94 V-2	natural
CTS-T-CV-16025	160	2.5	38	8	PA 66	UL94 V-2	natural
CTS-T-CV-20025	200	2.5	50	8	PA 66	UL94 V-2	natural
CTS-T-CV-14036	140	3.6	32	18	PA 66	UL94 V-2	natural
CTS-T-CV-20036	200	3.6	50	18	PA 66	UL94 V-2	natural
CTS-T-CV-29236	292	3.6	77	18	PA 66	UL94 V-2	natural
CTS-T-CV-20048	200	3.6	50	18	PA 66	UL94 V-2	natural
CTS-T-CV-30048	300	4.8	77	22	PA 66	UL94 V-2	natural
CTS-T-CV-36848	368	4.8	102	22	PA 66	UL94 V-2	natural
CTS-T-CV-20076	200	7.6	50	54	PA 66	UL94 V-2	natural
CTS-T-CV-36876	368	7.6	102	54	PA 66	UL94 V-2	natural