

CTS-TUV - High Temp. and UV Resistant Cable Tie



Details:

- **Polyamid 6.6, UL 94 V 2 (V0 on special order), heat-stabilized, UV resistant**
- **Color:** BLK - black
- Working temperature: -35°C to +110°C
- Short-time working temperature: up to +145°C
- Complies with: E 75050 (S) Spec.: UL appr.; Mil.Spec. 23190D
- Standard pack: 100 pcs

| Symbol | Length L | Width B | Max. cable bundle diameter | Breaking force | Material | Flammability | Color |
|--------------------|-------------|------------|----------------------------|----------------|----------|--------------|-------|
| | [mm] | [mm] | [mm] | [daN] | | | |
| CTS-T-CV-10025-UV | 100 | 2.5 | 20 | 8 | PA 66 | UL94 V-2 | black |
| CTS-T-CV-12025-UV | 120 | 2.5 | 25 | 8 | PA 66 | UL94 V-2 | black |
| CTS-T-CV-16025-UV | 160 | 2.5 | 38 | 8 | PA 66 | UL94 V-2 | black |
| CTS-T-CV-20025-UV | 200 | 2.5 | 50 | 8 | PA 66 | UL94 V-2 | black |
| CTS-T-CV-14036-UV | 140 | 3.6 | 32 | 18 | PA 66 | UL94 V-2 | black |
| CTS-T-CV-20036-UV | 200 | 3.6 | 50 | 18 | PA 66 | UL94 V-2 | black |
| CTS-T-CV-29236-UV | 292 | 3.6 | 77 | 18 | PA 66 | UL94 V-2 | black |
| CTS-T-CV-20048-UV | 200 | 3.6 | 50 | 18 | PA 66 | UL94 V-2 | black |
| CTS-T-CV-30048-UV | 300 | 4.8 | 77 | 22 | PA 66 | UL94 V-2 | black |
| CTS-T-CV-36848-UV | 368 | 4.8 | 102 | 22 | PA 66 | UL94 V-2 | black |
| CTS-T-CV- 36876-UV | 368 | 7.6 | 102 | 54 | PA 66 | UL94 V-2 | black |