

## CTS-UV - Standard Cable Tie, UV Resistant



### Details:

- **Polyamid 6.6, UL 94 V-2 (V-0 on special order)**
- **Color:** black
- UV resistant
- working temperature: -35°C do +85°C
- Complies with: E 75050 (S) Spec.: UL appr.; Mil.Spec. 23190D
- Standard pack: 100 pcs

Symbol	Length L	Width B	Max. cable bundle diameter	Breaking force	Material	Flammability	Color
	[mm]	[mm]	[mm]	[daN]			
CTS-8024-UV	80	2.4	15	8	PA 66	UL94 V-2	black
CTS-10025-UV	100	2.5	20	8.1	PA 66	UL94 V-2	black
CTS-12025-UV	120	2.5	25	8.1	PA 66	UL94 V-2	black
CTS-14025-UV	140	2.5	32	8.1	PA 66	UL94 V-2	black
CTS-16025-UV	160	2.5	38	8.1	PA 66	UL94 V-2	black
CTS-20025-UV	200	2.5	50	8.1	PA 66	UL94 V-2	black
CTS-14036-UV	140	3.6	32	18	PA 66	UL94 V-2	black
CTS-15036-UV	150	3.6	40	18	PA 66	UL94 V-2	black
CTS-20036-UV	200	3.6	50	18	PA 66	UL94 V-2	black
CTS-29236-UV	292	3.6	77	18	PA 66	UL94 V-2	black
CTS-37036-UV	370	3.6	102	18	PA 66	UL94 V-2	black
CTS-12048-UV	120	4.8	25	22	PA 66	UL94 V-2	black
CTS-16048-UV	160	4.8	38	22	PA 66	UL94 V-2	black
CTS-18848-UV	188	4.8	47	22	PA 66	UL94 V-2	black
CTS-20048-UV	200	4.8	50	22	PA 66	UL94 V-2	black
CTS-25048-UV	250	4.8	60	22	PA 66	UL94 V-2	black
CTS-30048-UV	300	4.8	77	22	PA 66	UL94 V-2	black
CTS-36848-UV	368	4.8	102	22	PA 66	UL94 V-2	black
CTS-43048-UV	430	4.8	110	22	PA 66	UL94 V-2	black
CTS-53048-UV	530	4.8	150	22	PA 66	UL94 V-2	black
CTS-15076-UV	150	7.6	38	54	PA 66	UL94 V-2	black
CTS-20076-UV	200	7.6	50	54	PA 66	UL94 V-2	black
CTS-29276-UV	292	7.6	77	54	PA 66	UL94 V-2	black

Symbol	Length L	Width B	Max. cable bundle diameter	Breaking force	Material	Flammability	Color
	[mm]	[mm]	[mm]	[daN]			
CTS-36876-UV	368	7.6	102	54	PA 66	UL94 V-2	black
CTS-45076-UV	450	7.6	128	54	PA 66	UL94 V-2	black
CTS-43090-UV	430	9	110	79.4	PA 66	UL94 V-2	black
CTS-53090-UV	530	9	140	79.4	PA 66	UL94 V-2	black
CTS-71090-UV	710	9	190	79.4	PA 66	UL94 V-2	black
CTS-77590-UV	775	9	228	79.4	PA 66	UL94 V-2	black
CTS-81090-UV	810	9	239	79.4	PA 66	UL94 V-2	black