

FP-6240 - PCB spacers



Details:

- **Material:** Nylon 6.6
- **Color:** natural
- Flammability: UL94V2
- Working temperature: -35°C up to +85°C

Symbol	Height A	B	C	D	Top mounting hole dia.	Top panel thickness range	Bottom mounting hole dia.	Bottom panel thickness range	Standard pack	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[szt./pcs]			
6240AA00	6.5	9.5	3	8.7	3.2	1.2 - 1.7	4.8	1.2 - 1.6	1000	PA 66	UL94 V-2	natural
6353AA00	7.9	9.5	3	8.7	3.2	1.2 - 1.7	4.8	1.2 - 1.6	1000	PA 66	UL94 V-2	natural
6241AA00	9.7	9.5	3	8.7	3.2	1.2 - 1.7	4.8	1.2 - 1.6	1000	PA 66	UL94 V-2	natural
6354AA00	11.1	9.5	3	8.7	3.2	1.2 - 1.7	4.8	1.2 - 1.6	1000	PA 66	UL94 V-2	natural
6242AA00	12.7	9.5	3	8.7	3.2	1.2 - 1.7	4.8	1.5 - 1.6	1000	PA 66	UL94 V-2	natural
6355AA00	14.3	9.5	3	8.7	3.2	1.2 - 1.7	4.8	1.2 - 1.6	1000	PA 66	UL94 V-2	natural
6356AA00	15.9	9.5	3	8.7	3.2	1.2 - 1.7	4.8	1.2 - 1.6	1000	PA 66	UL94 V-2	natural
5912AA00	3.5	10	3	10	4	1.2 - 1.7	5.5	0.8 - 1.6	1000	PA 66	UL94 V-2	natural
5913AA00	6.4	12.7	2.8	10	4	1.6	5.5	1.2 - 2.0	1000	PA 66	UL94 V-2	natural
5914AA00	6.3	10	3.1	10	4	1.6	5.5	1.0 - 1.7	1000	PA 66	UL94 V-2	natural
5915AA00	7.9	10	3.1	10	4	1.6	5.5	1.0 - 1.7	1000	PA 66	UL94 V-2	natural
5916AA00	10	10	3.1	10	4	1.6	5.5	1.0 - 1.7	1000	PA 66	UL94 V-2	natural
5917AA00	12	10	3.1	10	4	1.6	5.5	1.0 - 1.7	1000	PA 66	UL94 V-2	natural
5918AA00	12.7	10	3.1	10	4	1.6	5.5	1.0 - 1.7	1000	PA 66	UL94 V-2	natural
1199AA00	6.3	9.7	2.8	9.3	4.5	1.0 - 1.2	6.4	1.6	2500	PA 66	UL94 V-2	natural