




FP-6742 - Snap cable bushing



Details:

- **Material:** Nylon 6.6 UL94V2
- **Color:** black
- Working temperature: -35°C to +85°C
- Parts may appear with one or two fixing hooks per side

Symbol	A	B	C	D	Mounting hole diameter	Panel thickness range	Standard pack	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]						
6742AA01	9.5	5.2	1.6	8.2	8	0.8 - 1.8	1000	PA 66	UL94 V-2	black
6743AA01	12	6.6	1.6	10.3	9.5	0.8 - 3.3	1000	PA 66	UL94 V-2	black
6744AA01	13.6	8.4	1.6	10.3	11.1	0.8 - 3.3	1000	PA 66	UL94 V-2	black
6745AA01	15.1	9.8	1.6	10.3	13	0.8 - 3.3	1000	PA 66	UL94 V-2	black
6746AA01	18.2	12.8	1.6	10.3	16	0.8 - 3.3	1000	PA 66	UL94 V-2	black
6881AA01	20	12.7	1.6	10.3	17.5	0.8 - 3.3	2000	PA 66	UL94 V-2	black
6747AA01	21.5	14.3	1.6	11.3	19	0.8 - 3.3	2000	PA 66	UL94 V-2	black
6759AA01	23.8	19	1.4	6.3	22.2	0.8 - 1.6	1000	PA 66	UL94 V-2	black
6748AA01	25.1	18.6	1.6	11.2	22.2	0.8 - 3.3	1000	PA 66	UL94 V-2	black
6749AA01	27.8	19.4	1.6	10.8	25.4	0.8 - 3.3	1000	PA 66	UL94 V-2	black
6750AA01	34	24.5	1.6	11.7	30.1	0.8 - 3.3	1000	PA 66	UL94 V-2	black
6760AA01	38	26.2	1.6	11.5	34.2	1.0 - 3.1	1000	PA 66	UL94 V-2	black
6882AA01	38	30.4	1.6	11.5	34.2	1.0 - 3.1	1000	PA 66	UL94 V-2	black
6751AA01	37.8	25.8	1.6	11.3	35	0.8 - 3.5	1000	PA 66	UL94 V-2	black
6752AA01	41.2	33.3	1.6	11.6	38	1.0 - 3.3	1000	PA 66	UL94 V-2	black
6883AA01	53.8	41.8	1.6	11.4	50.8	0.8 - 3.2	500	PA 66	UL94 V-2	black

Symbol	A	B	C	D	Mounting hole diameter	Panel thickness range	Standard pack	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[szt./pcs]			
6884AA01	63	47.3	1.6	18.1	57.1	2.0 - 6.35	500	PA 66	UL94 V-2	black
6885AA01	67.5	50.5	1.6	18.1	63.5	2.0 - 6.35	500	PA 66	UL94 V-2	black