


FP-8584 - Metric thread cable glands



Details:

- Material: **Nylon 6 UL94V2**
- Color: **dark grey (RAL 7001), light grey (RAL 7035), black (RAL 9005)**
- Sealing ring in Polychloroprene - Nitrile CR/NBR.
- International Protection Marking: IP68
- Metric as per EN 60423
- Working temperature: -20°C to +100°C

Symbol	Metric thread A	Cable diameter range ØB	Thread length C	Wrench size D	E	F	Material	Flammability	Color	Standard pack
										[mm]
8584AA117001	M12×1.5	3.0 - 6.0	8	15	15	31	PA 6	UL94 V-2	dark gray	100
8585AA117001	M16×1.5	5.0 - 10.0	8	20	20	35.5	PA 6	UL94 V-2	dark gray	100
8586AA117001	M20×1.5	8.0 - 13.0	8	24	24	36	PA 6	UL94 V-2	dark gray	100
8587AA117001	M25×1.5	11.0 - 17.0	9	29	29	43	PA 6	UL94 V-2	dark gray	50
8588AA117001	M32×1.5	15.0 - 21.0	10	36	36	50	PA 6	UL94 V-2	dark gray	25
8589AA117001	M40×1.5	19.0 - 28.0	10	46	46	51	PA 6	UL94 V-2	dark gray	10
8590AA117001	M50×1.5	27.0 - 35.0	12	55	55	61.5	PA 6	UL94 V-2	dark gray	5
8591AA117001	M63×1.5	32.0 - 42.0	12	68	68	65.5	PA 6	UL94 V-2	dark gray	5
8592AA117035	M12×1.5	3.0 - 6.0	8	15	15	31	PA 6	UL94 V-2	light gray	100
8593AA117035	M16×1.5	5.0 - 10.0	8	20	20	35.5	PA 6	UL94 V-2	light gray	100
8594AA117035	M20×1.5	8.0 - 13.0	8	24	24	36	PA 6	UL94 V-2	light gray	100
8595AA117035	M25×1.5	11.0 - 17.0	9	29	29	43	PA 6	UL94 V-2	light gray	50
8596AA117035	M32×1.5	15.0 - 21.0	10	36	36	50	PA 6	UL94 V-2	light gray	25
8597AA117035	M40×1.5	19.0 - 28.0	10	46	46	51	PA 6	UL94 V-2	light gray	10

Symbol	Metric thread A	Cable diameter range ØB	Thread length C	Wrench size D	E	F	Material	Flammability	Color	Standard pack
		[mm]	[mm]	[mm]	[mm]	[mm]				[szt./pcs]
8598AA117035	M50×1.5	27.0 - 35.0	12	55	55	61.5	PA 6	UL94 V-2	light gray	5
8599AA117035	M63×1.5	32.0 - 42.0	12	68	68	65.5	PA 6	UL94 V-2	light gray	5
8600AA019005	M12×1.5	3.0 - 6.0	8	15	15	31	PA 6	UL94 V-2	black	100
8601AA019005	M16×1.5	5.0 - 10.0	8	20	20	35.5	PA 6	UL94 V-2	black	100
8602AA019005	M20×1.5	8.0 - 13.0	8	24	24	36	PA 6	UL94 V-2	black	100
8603AA019005	M25×1.5	11.0 - 17.0	9	29	29	43	PA 6	UL94 V-2	black	50
8604AA019005	M32×1.5	15.0 - 21.0	10	36	36	50	PA 6	UL94 V-2	black	25
8605AA019005	M40×1.5	19.0 - 28.0	10	46	46	51	PA 6	UL94 V-2	black	10
8606AA019005	M50×1.5	27.0 - 35.0	12	55	55	61.5	PA 6	UL94 V-2	black	5
8607AA019005	M63×1.5	32.0 - 42.0	12	68	68	65.5	PA 6	UL94 V-2	black	5