

FP-9758 - Snap rivet with knob



Details:

- **Material:** PA 6
- **Flammability:** UL94V2
- **Color:** black
- **Working temperature:** -35°C do +85°C

Symbol	A	B	C	Mounting hole diameter	Panel thickness range	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]	[mm]			
9758AA01	10	3.5	8	3.1	1.0 - 2.0	PA 6	UL94 V-2	natural
9759AA01	10	4.5	8	3.1	2.0 - 3.0	PA 6	UL94 V-2	natural
9760AA01	10	5.5	8	3.1	3.0 - 4.0	PA 6	UL94 V-2	natural
9761AA01	10	6.5	8	3.1	4.0 - 5.0	PA 6	UL94 V-2	natural
9762AA01	10	7.5	8	3.1	5.0 - 6.0	PA 6	UL94 V-2	natural
9763AA01	10	8	8	3.1	5.5 - 6.5	PA 6	UL94 V-2	natural
9764AA01	10	3.5	8	3.6	1.0 - 2.0	PA 6	UL94 V-2	natural
9765AA01	10	4.5	8	3.6	2.0 - 3.0	PA 6	UL94 V-2	natural
9766AA01	10	5.5	8	3.6	3.0 - 3.7	PA 6	UL94 V-2	natural
9767AA01	10	6	8	3.6	3.5 - 4.5	PA 6	UL94 V-2	natural
9768AA01	10	7	8	3.6	3.8 - 5.2	PA 6	UL94 V-2	natural
9769AA01	10	8	8	3.6	5.3 - 6.5	PA 6	UL94 V-2	natural
9780AA01	12	5	8	4.1	2.5 - 3.5	PA 6	UL94 V-2	natural
9781AA01	12	6	8	4.1	3.5 - 4.5	PA 6	UL94 V-2	natural
9782AA01	12	7	8	4.1	4.5 - 5.5	PA 6	UL94 V-2	natural
9783AA01	12	8	8	4.1	5.5 - 6.5	PA 6	UL94 V-2	natural
9784AA01	12	9	8	4.1	6.5 - 7.5	PA 6	UL94 V-2	natural

Symbol	A	B	C	Mounting hole diameter	Panel thickness range	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]	[mm]			
9785AA01	12	10	8	4.1	7.5 - 8.5	PA 6	UL94 V-2	natural