


H-HSRS6 - Nylon PCB self-retaining spacers



Details:

- **Material: Nylon 6/6 UL94 V-2**
- **Material Nylon 6/6 UL94 V-0 available on special order**
- **Colour: natural**
- **Temperature Range: -40°C to 85°C**
- #6 or M3 self-tapping screw
- Dimension A = thread depth
- Dimensions: ± 0.1 mm

Symbol	Height A	Panel thickness	Mounting hole diameter	Thread	Material	Flammability	Color
	[mm]						
H-10639	6.4	1.6	5.9	M3	PA 66	UL94 V-2	natural
H-10640	7.9	1.6	5.9	M3	PA 66	UL94 V-2	natural
H-10641	9.5	1.6	5.9	M3	PA 66	UL94 V-2	natural
H-10642	11.1	1.6	5.9	M3	PA 66	UL94 V-2	natural
H-10643	12.7	1.6	5.9	M3	PA 66	UL94 V-2	natural
H-10644	15.9	1.6	5.9	M3	PA 66	UL94 V-2	natural
H-10645	19.1	1.6	5.9	M3	PA 66	UL94 V-2	natural
H-10646	22.2	1.6	5.9	M3	PA 66	UL94 V-2	natural
H-10647	25.4	1.6	5.9	M3	PA 66	UL94 V-2	natural