

H-HST44 - Nylon Threaded Hex Supports



Details:

- **Material:** Nylon 6/6 UL94 V-2
- **Colour:** natural
- **Temperature Range:** -40°C to 85°C
- **Metric dimensions in brackets ± 0.1 mm**
- Recognized under the Component Program of Underwriters' Laboratories File F197049

Symbol	Height A	Int. thread	Int. thread length	Wrench size	Material	Flammability	Color
	[mm]		[mm]	[mm]			
H-12524	4.8	UNC 4-40	4.8	6.4	PA 66	UL94 V-2	natural
H-12525	6.4	UNC 4-40	6.4	6.4	PA 66	UL94 V-2	natural
H-12526	7.9	UNC 4-40	7.9	6.4	PA 66	UL94 V-2	natural
H-12527	9.5	UNC 4-40	9.5	6.4	PA 66	UL94 V-2	natural
H-12528	11.1	UNC 4-40	11.1	6.4	PA 66	UL94 V-2	natural
H-12529	12.7	UNC 4-40	12.7	6.4	PA 66	UL94 V-2	natural
H-12530	14.3	UNC 4-40	14.3	6.4	PA 66	UL94 V-2	natural
H-12531	15.9	UNC 4-40	15.9	6.4	PA 66	UL94 V-2	natural
H-12532	19.1	UNC 4-40	19.1	6.4	PA 66	UL94 V-2	natural
H-12533	22.2	UNC 4-40	22.2	6.4	PA 66	UL94 V-2	natural
H-12534	25.4	UNC 4-40	25.4	6.4	PA 66	UL94 V-2	natural