

H-HST64 - Nylon Threaded Hex Supports



Details:

- **Material:** Nylon 6/6 UL94 V-2
- **Colour:** natural
- **Temperature Range:** -40°C to 85°C
- **Metric dimensions in brackets ± 0.1 mm**
- Recognized under the Component Program of Underwriters' Laboratories File F197049

Symbol	Height A	Int. thread	Int. thread length	Wrench size	Material	Flammability	Color
	[mm]		[mm]	[mm]			
H-12552	4.8	#6-32	4.8	6.4	PA 66	UL94 V-2	natural
H-12553	6.4	#6-32	6.4	6.4	PA 66	UL94 V-2	natural
H-12554	7.9	#6-32	7.9	6.4	PA 66	UL94 V-2	natural
H-12555	9.5	#6-32	9.5	6.4	PA 66	UL94 V-2	natural
H-12556	11.1	#6-32	11.1	6.4	PA 66	UL94 V-2	natural
H-12557	12.7	#6-32	12.7	6.4	PA 66	UL94 V-2	natural
H-12558	14.3	#6-32	14.3	6.4	PA 66	UL94 V-2	natural
H-12559	15.9	#6-32	15.9	6.4	PA 66	UL94 V-2	natural
H-12560	19.1	#6-32	19.1	6.4	PA 66	UL94 V-2	natural
H-12561	22.2	#6-32	22.2	6.4	PA 66	UL94 V-2	natural
H-12562	25.4	#6-32	25.4	6.4	PA 66	UL94 V-2	natural