

## H-HSTM35 - Nylon Threaded Hex Supports



### Details:

- **Material:** Nylon 6/6 UL94 V-2
- **Colour:** natural
- **Temperature Range:** -40°C to 85°C
- **Metric dimensions in brackets  $\pm 0.1$  mm**
- H-12858, H-12588 and H-12590 available on special order
- Recognized under the Component Program of Underwriters' Laboratories File F197049

| Symbol  | Height<br>A | Int. thread | Int. thread length | Wrench size | Material | Flammability | Color   |
|---------|-------------|-------------|--------------------|-------------|----------|--------------|---------|
|         | [mm]        |             | [mm]               | [mm]        |          |              |         |
| H-12584 | 6           | M3          | 6                  | 5           | PA 66    | UL94 V-2     | natural |
| H-12585 | 6.4         | M3          | 6.4                | 5           | PA 66    | UL94 V-2     | natural |
| H-12586 | 8           | M3          | 8                  | 5           | PA 66    | UL94 V-2     | natural |
| H-12587 | 10          | M3          | 10                 | 5           | PA 66    | UL94 V-2     | natural |
| H-12588 | 11          | M3          | 11                 | 5           | PA 66    | UL94 V-2     | natural |
| H-12589 | 12          | M3          | 12                 | 5           | PA 66    | UL94 V-2     | natural |
| H-12590 | 13          | M3          | 13                 | 5           | PA 66    | UL94 V-2     | natural |
| H-12592 | 15          | M3          | 15                 | 5           | PA 66    | UL94 V-2     | natural |
| H-12594 | 18          | M3          | 18                 | 5           | PA 66    | UL94 V-2     | natural |
| H-12595 | 20          | M3          | 20                 | 5           | PA 66    | UL94 V-2     | natural |
| H-12596 | 25          | M3          | 25                 | 5           | PA 66    | UL94 V-2     | natural |