




H-LTPEP - Brass Pressure Equalization and Drain Plugs




Typ 1
Type 1



Typ 2
Type 2



Typ 3
Type 3



Otwór odpływowy
Clearance hole

Details:

- **Material:** Nickel-Plated Brass
- **Temperature Range:** -40°C to 110°C
- IP Rating:
 - Membrane - IP66/IP68/IP69
 - Filter Disc - IP55/IPX9K
 - Drainage Element - IP4X
- **Type 1:** Liquid Tight Pressure Equalization Plugs - Ultimate in Liquid Tight Pressure Equalization, also available with certified in accordance with IECEx and ATEX
- **Type 2:** Liquid Resistant Pressure Equalization Plugs - Maximize Airflow for Extreme Pressure and Moisture Fluctuations
- **Type 3:** Threaded Drain Plug - For Applications Where Condensation Is Expected
- Drainage Plug Brass Locknuts ([H-DPLN](#)) sold separately

Symbol	Type	Ext. thread	Mounting hole diameter A	B	C	D	Protection class	Material
			[mm]					
H-4350	1	M12×1.5	12	17.5	8	18	IP 66, 67, 68	brass, nickel plated
H-4351	1	M16×1.5	16	17.5	8	18	IP 66, 67, 68	brass, nickel plated
H-4352	1	M20×1.5	20	18	8	22	IP 66, 67, 68	brass, nickel plated
H-4354	2	M12×1.5	12	17.5	8	18	IP 55, X9K	brass, nickel plated
H-4355	2	M16×1.5	16	17.5	8	18	IP 55, X9K	brass, nickel plated
H-4356	2	M20×1.5	20	18	8	22	IP 55, X9K	brass, nickel plated
H-4357	3	M12×1.5	12	19.5	10	18	IP4X	brass, nickel plated
H-4358	3	M16×1.5	16	19.5	10	18	IP4X	brass, nickel plated
H-4359	3	M20×1.5	20	20	10	22	IP4X	brass, nickel plated