





## H-OCB - Open/Closed Bushings



**Maks. grubość panelu: 3.2 lub 6.4 mm**  
*Max. panel thickness: 3.2 or 6.4 mm*

**Maks. grubość panelu: 1.6 mm**  
*Max. panel thickness: 1.6 mm*

### Details:

- **Material: Nylon 6/6 UL94 V-2**
- **Colour: black (white and other colours available on special order)**
- **Temperature Range: -18°C to 105°C**

Symbol	Mounting hole diameter	Int. diameter A	Int. diameter B	Height C	Panel thickness range	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]	[mm]			
H-2934	7	5.6	8.9	6	1.6 max.	PA 66	UL94 V-2	black
H-2938	13	9.7	14.2	6.4	1.6 max.	PA 66	UL94 V-2	black
H-2941	16	13.2	18	6.4	1.6 max.	PA 66	UL94 V-2	black
H-2943	19	16	21.1	6.4	1.6 max.	PA 66	UL94 V-2	black
H-2945	22	19.1	24.9	6.4	1.6 max.	PA 66	UL94 V-2	black
H-2947	24	20.8	26.9	6.4	1.6 max.	PA 66	UL94 V-2	black
H-2950	27	24.8	28.7	6.5	1.6 max.	PA 66	UL94 V-2	black
H-2865	9.5	6.7	10.7	9.9	3.2 max.	PA 66	UL94 V-2	black
H-2867	11.1	8.4	12.7	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2871	12.7	7.9	14.3	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2875	13	9	14.9	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2869	14.3	9.9	16.3	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2872	15.9	11.1	17.5	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2914	16.5	12.3	18.6	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2873	19.1	12.7	19.8	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2917	22	17.3	24.8	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2874	22.2	17	23.4	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2920	25	20.4	26.4	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2878	25.4	19.1	26.6	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2879	27.8	20.6	29.4	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2881	31.8	25.8	34.1	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2882	34.9	25.4	37.3	10.3	3.2 max.	PA 66	UL94 V-2	black
H-2883	38.1	26.9	40.1	10.7	3.2 max.	PA 66	UL94 V-2	black
H-2900	50.8	43.9	53.9	10.7	3.2 max.	PA 66	UL94 V-2	black

Symbol	Mounting hole diameter	Int. diameter A	Int. diameter B	Height C	Panel thickness range	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]	[mm]			
H-2909	63.5	50.8	66	18.3	6.4 max.	PA 66	UL94 V-2	black