




## H-PGS - Continuous Grommet Rolls



**Nieząbkowana**  
Unserrated



**Ząbkowana**  
Serrated



Details:

- **Material: Polyethylene or Nylon**
- **Flammability Rating: UL94 HB**
- **Colour: natural or black**
- Temperature Range:
  - Polyethylene: -40°C to 65°C
  - Nylon: -40°C to 85°C
- Grommet Strips protect against damage from sharp panel edges.
- Ideal for tight radii or irregular panel holes and cut-outs.
- Roll length: 30.5m (100 feet)

Symbol	Panel thickness range	A [mm]	B [mm]	C [mm]	Serrated	Adhesive	Material	Flammability	Color
	[mm]								
H-12391	0.9 - 1.8	4.4	0.8	2.8	no	no	PE	UL94 HB	natural
H-12391B	0.9 - 1.8	4.4	0.8	2.8	no	no	PE	UL94 HB	black
H-12392	1.8 - 2.7	4.4	0.8	2.8	no	no	PE	UL94 HB	natural
H-12392B	1.8 - 2.7	4.4	0.8	2.8	no	no	PE	UL94 HB	black
H-12393	2.7 - 4.2	4.8	1.2	4	no	no	PE	UL94 HB	natural
H-12393B	2.7 - 4.2	4.8	1.2	4	no	no	PE	UL94 HB	black
H-12395	0.9 - 1.8	4.1	0.6	1.5	no	yes	PE	UL94 HB	natural
H-12395B	0.9 - 1.8	4.1	0.6	1.5	no	yes	PE	UL94 HB	black
H-12396	0.9 - 1.8	4.4	0.8	2.8	no	yes	PE	UL94 HB	natural
H-12396B	0.9 - 1.8	4.4	0.8	2.8	no	yes	PE	UL94 HB	black
H-12397	1.8 - 2.7	4.4	0.8	2.8	no	yes	PE	UL94 HB	natural
H-12397B	1.8 - 2.7	4.4	0.8	2.8	no	yes	PE	UL94 HB	black
H-12398	2.7 - 4.2	4.8	1.2	4	no	yes	PE	UL94 HB	natural
H-12398B	2.7 - 4.2	4.8	1.2	4	no	yes	PE	UL94 HB	black
H-12399	0.7 - 0.9	3.2	0.8	0.8	yes	no	PE	UL94 HB	natural
H-12399B	0.7 - 0.9	3.2	0.8	0.8	yes	no	PE	UL94 HB	black
H-12400	0.9 - 1.8	4.4	0.8	2.8	yes	no	PE	UL94 HB	natural
H-12400B	0.9 - 1.8	4.4	0.8	2.8	yes	no	PE	UL94 HB	black
H-12401	1.8 - 2.7	4.4	0.8	2.8	yes	no	PE	UL94 HB	natural

Symbol	Panel thickness range	A	B	C	Serrated	Adhesive	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]					
H-12401B	1.8 - 2.7	4.4	0.8	2.8	yes	no	PE	UL94 HB	black
H-12402	2.7 - 4.2	4.8	1.2	4	yes	no	PE	UL94 HB	natural
H-12402B	2.7 - 4.2	4.8	1.2	4	yes	no	PE	UL94 HB	black
H-12405	0.9 - 1.8	4.1	0.6	1.5	yes	yes	PE	UL94 HB	natural
H-12405B	0.9 - 1.8	4.1	0.6	1.5	yes	yes	PE	UL94 HB	black
H-12406	0.9 - 1.8	4.4	0.8	2.8	yes	yes	PE	UL94 HB	natural
H-12406B	0.9 - 1.8	4.4	0.8	2.8	yes	yes	PE	UL94 HB	black
H-12407	1.8 - 2.7	4.4	0.8	2.8	yes	yes	PE	UL94 HB	natural
H-12407B	1.8 - 2.7	4.4	0.8	2.8	yes	yes	PE	UL94 HB	black
H-12411	0.7 - 0.9	3.2	0.8	0.8	no	no	PA	UL94 HB	natural
H-12411B	0.7 - 0.9	3.2	0.8	0.8	no	no	PA	UL94 HB	black
H-12412	0.9 - 1.8	4.4	0.8	2.8	no	no	PA	UL94 HB	natural
H-12412B	0.9 - 1.8	4.4	0.8	2.8	no	no	PA	UL94 HB	black
H-12416	0.9 - 1.8	4.4	0.8	2.8	no	yes	PA	UL94 HB	natural
H-12416B	0.9 - 1.8	4.4	0.8	2.8	no	yes	PA	UL94 HB	black
H-12417	1.8 - 2.7	4.4	0.8	2.8	no	yes	PA	UL94 HB	natural
H-12417B	1.8 - 2.7	4.4	0.8	2.8	no	yes	PA	UL94 HB	black
H-12418	2.7 - 4.2	4.8	1.2	4	no	yes	PA	UL94 HB	natural
H-12418B	2.7 - 4.2	4.8	1.2	4	no	yes	PA	UL94 HB	black
H-12419	0.7 - 0.9	3.2	0.8	0.8	yes	no	PA	UL94 HB	natural
H-12419B	0.7 - 0.9	3.2	0.8	0.8	yes	no	PA	UL94 HB	black
H-12420	0.9 - 1.8	4.4	0.8	2.8	yes	no	PA	UL94 HB	natural
H-12420B	0.9 - 1.8	4.4	0.8	2.8	yes	no	PA	UL94 HB	black
H-12421	1.8 - 2.7	4.4	0.8	2.8	yes	no	PA	UL94 HB	natural
H-12421B	1.8 - 2.7	4.4	0.8	2.8	yes	no	PA	UL94 HB	black
H-12422	2.7 - 4.2	4.8	1.2	4	yes	no	PA	UL94 HB	natural
H-12422B	2.7 - 4.2	4.8	1.2	4	yes	no	PA	UL94 HB	black
H-12426	0.9 - 1.8	4.4	0.8	2.8	yes	yes	PA	UL94 HB	natural
H-12426B	0.9 - 1.8	4.4	0.8	2.8	yes	yes	PA	UL94 HB	black
H-12427	1.8 - 2.7	4.4	0.8	2.8	yes	yes	PA	UL94 HB	natural
H-12427B	1.8 - 2.7	4.4	0.8	2.8	yes	yes	PA	UL94 HB	black