

M-NSU80 - Articulating Adjustable Feet with fixing system



Details:

- **Material: stainless steel**
- Base diameter: 80 mm
- Max. static load: 10000 N

Symbol	A	Stud length B	Base diameter D	Wrench size	Metric thread F	Base height G	Height H	I
	[mm]	[mm]	[mm]	[mm]		[mm]	[mm]	[mm]
M-NSU80-M16-075	38	75	80	13	M16	25	113	54
M-NSU80-M16-100	38	100	80	13	M16	25	138	54
M-NSU80-M16-125	38	125	80	13	M16	25	163	54
M-NSU80-M16-150	38	150	80	13	M16	25	188	54
M-NSU80-M16-175	38	175	80	13	M16	25	213	54
M-NSU80-M16-200	38	200	80	13	M16	25	235	54
M-NSU80-M20-075	38	75	80	17	M20	25	113	54
M-NSU80-M20-100	38	100	80	17	M20	25	138	54
M-NSU80-M20-125	38	125	80	17	M20	25	163	54
M-NSU80-M20-150	38	150	80	17	M20	25	188	54
M-NSU80-M20-175	38	175	80	17	M20	25	213	54
M-NSU80-M20-200	38	200	80	17	M20	25	238	54
M-NSU80-M20-225	38	225	80	17	M20	25	260	54
M-NSU80-M20-250	38	250	80	17	M20	25	285	54
M-NSU80-M24-075	40	75	80	20	M24	25	115	54
M-NSU80-M24-100	40	100	80	20	M24	25	140	54
M-NSU80-M24-125	40	125	80	20	M24	25	165	54
M-NSU80-M24-150	40	150	80	20	M24	25	190	54
M-NSU80-M24-175	40	175	80	20	M24	25	215	54
M-NSU80-M24-200	40	200	80	20	M24	25	240	54
M-NSU80-M24-225	40	225	80	20	M24	25	265	54