


O-MDLA-M - Brass Cable Gland - Metric Thread

DŁUGOŚĆ GWINTU



Details:

- **Material: Brass, Nickel Plated**
- Protection Rating IP68
- Locknut and sealing washer available separately
- Operating temperature range: -20°C to + 85°C
- CE approved

Symbol	Metric thread	Thread length	Cable diameter range	Material	Standard pack
		[mm]	[mm]		[szt./pcs]
O-MDLA-M12-3	M12×1.5	6.5	3.0 - 6.5	brass, nickel plated	25
O-MDLA-M12-2	M12×1.5	6.5	2.0 - 5.0	brass, nickel plated	25
O-MDLA-M16-4	M16×1.5	8	4.0 - 8.0	brass, nickel plated	25
O-MDLA-M16-2	M16×1.5	8	2.0 - 6.0	brass, nickel plated	25
O-MDLA-M20-6	M20×1.5	6.5	6.0 - 12.0	brass, nickel plated	25
O-MDLA-M20-5	M20×1.5	6.5	5.0 - 9.0	brass, nickel plated	25
O-MDLA-M25-13	M25×1.5	8	13.0 - 18.0	brass, nickel plated	25
O-MDLA-M25-9	M25×1.5	8	9.0 - 16.0	brass, nickel plated	25
O-MDLA-M32-18	M32×1.5	10	18.0 - 25.0	brass, nickel plated	10
O-MDLA-M32-13	M32×1.5	10	13.0 - 20.0	brass, nickel plated	10
O-MDLA-M40-22	M40×1.5	10	22.0 - 32.0	brass, nickel plated	10
O-MDLA-M40-20	M40×1.5	10	20.0 - 26.0	brass, nickel plated	10
O-MDLA-M50-32	M50×1.5	13	32.0 - 38.0	brass, nickel plated	10
O-MDLA-M50-25	M50×1.5	13	25.0 - 31.0	brass, nickel plated	10
O-MDLA-M63-37	M63×1.5	10.5	37.0 - 44.0	brass, nickel plated	10
O-MDLA-M63-29	M63×1.5	10.5	29.0 - 35.0	brass, nickel plated	10