


O-MDLA-PG - Brass Cable Gland - PG Thread

DŁUGOŚĆ GWINTU



Details:

- **Material: Brass, Nickel Plated**
- Protection Rating IP68
- Locknut and sealing washer available separately
- Operating temperature range: -20°C to + 85°C
- CE approved

Symbol	PG thread	Thread length	Cable diameter range	Material	Standard pack
		[mm]	[mm]		[szt./pcs]
O-MDLA-PG-7-3	PG7	7	3.0 - 6.5	brass, nickel plated	25
O-MDLA-PG-7-2	PG7	7	2.0 - 5.0	brass, nickel plated	25
O-MDLA-PG-9-4	PG9	7	4.0 - 8.0	brass, nickel plated	25
O-MDLA-PG-9-2	PG9	7	2.0 - 6.0	brass, nickel plated	25
O-MDLA-PG-11-5	PG11	7	5.0 - 10.0	brass, nickel plated	25
O-MDLA-PG-13.5-6	PG13.5	7	6.0 - 12.0	brass, nickel plated	25
O-MDLA-PG-13.5-5	PG13.5	7	5.0 - 9.0	brass, nickel plated	25
O-MDLA-PG-16-10	PG16	6.5	10.0 - 14.0	brass, nickel plated	25
O-MDLA-PG-16-7	PG16	6.5	7.0 - 12.0	brass, nickel plated	25
O-MDLA-PG-21-13	PG21	8	13.0 - 18.0	brass, nickel plated	25
O-MDLA-PG-21-9	PG21	8	9.0 - 16.0	brass, nickel plated	25
O-MDLA-PG-29-18	PG29	9	18.0 - 25.0	brass, nickel plated	10
O-MDLA-PG-29-13	PG29	9	13.0 - 20.0	brass, nickel plated	10
O-MDLA-PG-36-22	PG36	10.5	22.0 - 32.0	brass, nickel plated	10
O-MDLA-PG-36-20	PG36	10.5	20.0 - 26.0	brass, nickel plated	10
O-MDLA-PG-42-32	PG42	11.5	32.0 - 38.0	brass, nickel plated	10
O-MDLA-PG-42-25	PG42	11.5	25.0 - 31.0	brass, nickel plated	10
O-MDLA-PG-48-37	PG48	13	37.0 - 44.0	brass, nickel plated	10
O-MDLA-PG-48-29	PG48	13	29.0 - 35.0	brass, nickel plated	10