

## O-SSPZ - Steel Levelling Feet



### Details:

- **Material: steel with various finishes (see table)**
- 15° swivel to adjust to uneven surfaces
- Hardened ball (except in stainless) forms its own seat and resists galling
- Large diameter pad for solid support

| Symbol           | Foot            | Type   | Finish        | Metric thread | Stud length | Base diameter D | Base height h | Approx. load capacity |
|------------------|-----------------|--------|---------------|---------------|-------------|-----------------|---------------|-----------------------|
|                  |                 |        |               |               | [mm]        |                 |               |                       |
| O-SSPZ-M6-T-CR   | standard        | stud   | gold chromate | M6            | 25.4        | 19.1            | 13.5          | 13.5 kg kg            |
| O-SSPZE-M6-T-CR  | with rubber pad | stud   | gold chromate | M6            | 25.4        | 19.1            | 13.5          | 310 kg                |
| O-SSPZ-M8-T-CR   | standard        | stud   | gold chromate | M8            | 31.8        | 25.4            | 17.8          | 490 kg                |
| O-SSPZE-M8-T-CR  | with rubber pad | stud   | gold chromate | M8            | 31.8        | 25.4            | 17.8          | 490 kg                |
| O-SSPZ-M10-T-CR  | standard        | stud   | gold chromate | M10           | 51          | 32              | 22            | 1700 kg               |
| O-SSPZE-M10-T-CR | with rubber pad | stud   | gold chromate | M10           | 51          | 32              | 22            | 1700 kg               |
| O-SSPZ-M12-T-CR  | standard        | stud   | gold chromate | M12           | 51          | 48              | 29            | 2260 kg               |
| O-SSPZE-M12-T-CR | with rubber pad | stud   | gold chromate | M12           | 51          | 48              | 29            | 2260 kg               |
| O-SSPZ-M16-T-CR  | standard        | stud   | gold chromate | M16           | 51          | 64              | 32            | 2720 kg               |
| O-SSPZE-M16-T-CR | with rubber pad | stud   | gold chromate | M16           | 51          | 64              | 32            | 2720 kg               |
| O-SSPZ-M20-T-CR  | standard        | stud   | gold chromate | M20           | 51          | 76              | 38            | 3260 kg               |
| O-SSPZE-M20-T-CR | with rubber pad | stud   | gold chromate | M20           | 51          | 76              | 38            | 3260 kg               |
| O-SSPZ-M24-T-CR  | standard        | stud   | gold chromate | M24           | 108         | 102             | 48            | 9970 kg               |
| O-SSPZE-M24-T-CR | with rubber pad | stud   | gold chromate | M24           | 108         | 102             | 48            | 9970 kg               |
| O-SSPZ-M6-G-CR   | standard        | socket | gold chromate | M6            | -           | 19.1            | 13.5          | 310 kg                |
| O-SSPZE-M6-G-CR  | with rubber pad | socket | gold chromate | M6            | -           | 19.1            | 13.5          | 310 kg                |

| Symbol           | Foot            | Type   | Finish          | Metric thread | Stud length | Base diameter D | Base height h | Approx. load capacity |
|------------------|-----------------|--------|-----------------|---------------|-------------|-----------------|---------------|-----------------------|
|                  |                 |        |                 |               | [mm]        | [mm]            | [mm]          |                       |
| O-SSPZ-M8-G-CR   | standard        | socket | gold chromate   | M8            | -           | 25.4            | 17.8          | 490 kg                |
| O-SSPZE-M8-G-CR  | with rubber pad | socket | gold chromate   | M8            | -           | 25.4            | 17.8          | 490 kg                |
| O-SSPZ-M10-G-CR  | standard        | socket | gold chromate   | M10           | -           | 32              | 22            | 1700 kg               |
| O-SSPZE-M10-G-CR | with rubber pad | socket | gold chromate   | M10           | -           | 32              | 22            | 1700 kg               |
| O-SSPZ-M12-G-CR  | standard        | socket | gold chromate   | M12           | -           | 48              | 29            | 2260 kg               |
| O-SSPZE-M12-G-CR | with rubber pad | socket | gold chromate   | M12           | -           | 48              | 29            | 2260 kg               |
| O-SSPZ-M16-G-CR  | standard        | socket | gold chromate   | M16           | -           | 64              | 32            | 2720 kg               |
| O-SSPZE-M16-G-CR | with rubber pad | socket | gold chromate   | z             | -           | 64              | 32            | 2720 kg               |
| O-SSPZ-M20-G-CR  | standard        | socket | gold chromate   | M20           | -           | 76              | 38            | 3260 kg               |
| O-SSPZE-M20-G-CR | with rubber pad | socket | gold chromate   | M20           | -           | 76              | 38            | 3260 kg               |
| O-SSPZ-M24-G-CR  | standard        | socket | gold chromate   | M24           | -           | 102             | 48            | 9970 kg               |
| O-SSPZE-M24-G-CR | with rubber pad | socket | gold chromate   | M24           | -           | 102             | 48            | 9970 kg               |
| O-SSPZ-M6-T-NI   | standard        | stud   | nickel plated   | M6            | 25.4        | 19.1            | 13.5          | 310 kg                |
| O-SSPZE-M6-T-NI  | with rubber pad | stud   | nickel plated   | M6            | 25.4        | 19.1            | 13.5          | 310 kg                |
| O-SSPZ-M8-T-NI   | standard        | stud   | nickel plated   | M8            | 31.8        | 25.4            | 17.8          | 490 kg                |
| O-SSPZE-M8-T-NI  | with rubber pad | stud   | nickel plated   | M8            | 31.8        | 25.4            | 17.8          | 490 kg                |
| O-SSPZ-M10-T-NI  | standard        | stud   | nickel plated   | M10           | 51          | 32              | 22            | 1700 kg               |
| O-SSPZE-M10-T-NI | with rubber pad | stud   | nickel plated   | M10           | 51          | 32              | 22            | 1700 kg               |
| O-SSPZ-M12-T-NI  | standard        | stud   | nickel plated   | M12           | 51          | 48              | 29            | 2260 kg               |
| O-SSPZE-M12-T-NI | with rubber pad | stud   | nickel plated   | M12           | 51          | 48              | 29            | 2260 kg               |
| O-SSPZ-M16-T-NI  | standard        | stud   | nickel plated   | M16           | 51          | 64              | 32            | 2720 kg               |
| O-SSPZE-M16-T-NI | with rubber pad | stud   | nickel plated   | M16           | 51          | 64              | 32            | 2720 kg               |
| O-SSPZ-M20-T-NI  | standard        | stud   | nickel plated   | M20           | 51          | 76              | 38            | 3260 kg               |
| O-SSPZE-M20-T-NI | with rubber pad | stud   | nickel plated   | M20           | 51          | 76              | 38            | 3260 kg               |
| O-SSPZ-M24-T-NI  | standard        | stud   | nickel plated   | M24           | 108         | 102             | 48            | 9970 kg               |
| O-SSPZE-M24-T-NI | with rubber pad | stud   | nickel plated   | M24           | 108         | 102             | 48            | 9970 kg               |
| O-SSPZ-M6-G-NI   | standard        | socket | nickel plated   | M6            | -           | 19.1            | 13.5          | 310 kg                |
| O-SSPZE-M6-G-NI  | with rubber pad | socket | nickel plated   | M6            | -           | 19.1            | 13.5          | 310 kg                |
| O-SSPZ-M8-G-NI   | standard        | socket | nickel plated   | M8            | -           | 25.4            | 17.8          | 490 kg                |
| O-SSPZE-M8-G-NI  | with rubber pad | socket | nickel plated   | M8            | -           | 25.4            | 17.8          | 490 kg                |
| O-SSPZ-M10-G-NI  | standard        | socket | nickel plated   | M10           | -           | 32              | 22            | 1700 kg               |
| O-SSPZE-M10-G-NI | with rubber pad | socket | nickel plated   | M10           | -           | 32              | 22            | 1700 kg               |
| O-SSPZ-M12-G-NI  | standard        | socket | nickel plated   | M12           | -           | 48              | 29            | 2260 kg               |
| O-SSPZE-M12-G-NI | with rubber pad | socket | nickel plated   | M12           | -           | 48              | 29            | 2260 kg               |
| O-SSPZ-M16-G-NI  | standard        | socket | nickel plated   | M16           | -           | 64              | 32            | 2720 kg               |
| O-SSPZE-M16-G-NI | with rubber pad | socket | nickel plated   | M16           | -           | 64              | 32            | 2720 kg               |
| O-SSPZ-M20-G-NI  | standard        | socket | nickel plated   | M20           | -           | 76              | 38            | 3260 kg               |
| O-SSPZE-M20-G-NI | with rubber pad | socket | nickel plated   | M20           | -           | 76              | 38            | 3260 kg               |
| O-SSPZ-M24-G-NI  | standard        | socket | nickel plated   | M24           | -           | 102             | 48            | 9970 kg               |
| O-SSPZE-M24-G-NI | with rubber pad | socket | nickel plated   | M24           | -           | 102             | 48            | 9970 kg               |
| O-SSPZ-M6-T-SS   | standard        | stud   | stainless steel | M6            | 25.4        | 19.1            | 13.5          | 310 kg                |
| O-SSPZE-M6-T-SS  | with rubber pad | stud   | stainless steel | M6            | 25.4        | 19.1            | 13.5          | 310 kg                |
| O-SSPZ-M8-T-SS   | standard        | stud   | stainless steel | M8            | 31.8        | 25.4            | 17.8          | 490 kg                |
| O-SSPZE-M8-T-SS  | with rubber pad | stud   | stainless steel | M8            | 31.8        | 25.4            | 17.8          | 490 kg                |
| O-SSPZ-M10-T-SS  | standard        | stud   | stainless steel | M10           | 51          | 32              | 22            | 1700 kg               |
| O-SSPZE-M10-T-SS | with rubber pad | stud   | stainless steel | M10           | 51          | 32              | 22            | 1700 kg               |
| O-SSPZ-M12-T-SS  | standard        | stud   | stainless steel | M12           | 51          | 48              | 29            | 2260 kg               |
| O-SSPZE-M12-T-SS | with rubber pad | stud   | stainless steel | M12           | 51          | 48              | 29            | 2260 kg               |
| O-SSPZ-M16-T-SS  | standard        | stud   | stainless steel | M16           | 51          | 64              | 32            | 2720 kg               |
| O-SSPZE-M16-T-SS | with rubber pad | stud   | stainless steel | M16           | 51          | 64              | 32            | 2720 kg               |
| O-SSPZ-M20-T-SS  | standard        | stud   | stainless steel | M20           | 51          | 76              | 38            | 3260 kg               |
| O-SSPZE-M20-T-SS | with rubber pad | stud   | stainless steel | M20           | 51          | 76              | 38            | 3260 kg               |
| O-SSPZ-M24-T-SS  | standard        | stud   | stainless steel | M24           | 108         | 102             | 48            | 9970 kg               |
| O-SSPZE-M24-T-SS | with rubber pad | stud   | stainless steel | M24           | 108         | 102             | 48            | 9970 kg               |

| Symbol           | Foot            | Type   | Finish          | Metric thread | Stud length | Base diameter D | Base height h | Approx. load capacity |
|------------------|-----------------|--------|-----------------|---------------|-------------|-----------------|---------------|-----------------------|
|                  |                 |        |                 |               | [mm]        |                 |               |                       |
| O-SSPZ-M6-G-SS   | standard        | socket | stainless steel | M6            | -           | 19.1            | 13.5          | 310 kg                |
| O-SSPZE-M6-G-SS  | with rubber pad | socket | stainless steel | M6            | -           | 19.1            | 13.5          | 310 kg                |
| O-SSPZ-M8-G-SS   | standard        | socket | stainless steel | M8            | -           | 25.4            | 17.8          | 490 kg                |
| O-SSPZE-M8-G-SS  | with rubber pad | socket | stainless steel | M8            | -           | 25.4            | 17.8          | 490 kg                |
| O-SSPZ-M10-G-SS  | standard        | socket | stainless steel | M10           | -           | 32              | 22            | 1700 kg               |
| O-SSPZE-M10-G-SS | with rubber pad | socket | stainless steel | M10           | -           | 32              | 22            | 1700 kg               |
| O-SSPZ-M12-G-SS  | standard        | socket | stainless steel | M12           | -           | 48              | 29            | 2260 kg               |
| O-SSPZE-M12-G-SS | with rubber pad | socket | stainless steel | M12           | -           | 48              | 29            | 2260 kg               |
| O-SSPZ-M16-G-SS  | standard        | socket | stainless steel | M16           | -           | 64              | 32            | 2720 kg               |
| O-SSPZE-M16-G-SS | with rubber pad | socket | stainless steel | M16           | -           | 64              | 32            | 2720 kg               |
| O-SSPZ-M20-G-SS  | standard        | socket | stainless steel | M20           | -           | 76              | 38            | 3260 kg               |
| O-SSPZE-M20-G-SS | with rubber pad | socket | stainless steel | M20           | -           | 76              | 38            | 3260 kg               |
| O-SSPZ-M24-G-SS  | standard        | socket | stainless steel | M24           | -           | 102             | 48            | 9970 kg               |
| O-SSPZE-M24-G-SS | with rubber pad | socket | stainless steel | M24           | -           | 102             | 48            | 9970 kg               |