

O-WKWG - Heavy Duty Square Threaded Inserts



Details:

- **Body material:** Nylon
- **Insert material:** Nickel Plated Brass or Stainless Steel
- **Color:** black
- Interference fit
- Designed for use with machine feet
- Heavy duty for high load capacity

Symbol	Gauge	Thread	D	D ₁	H	H ₁	Max. load static [N]	Standard pack [szt./pcs]	Material	Insert material	Color
			[mm]	[mm]	[mm]	[mm]					
O-WKWG-B-M10-15-30	1.5	M10	30	27.5	6	33	5500	24	PA	nickel plated brass	black
O-WKWG-S-M10-15-30	1.5	M10	30	27.5	6	33	5500	24	PA	stainless steel	black
O-WKWG-B-M10-15-40	1.5	M10	40	37.5	8	43	8000	24	PA	nickel plated brass	black
O-WKWG-S-M10-15-40	1.5	M10	40	37.5	8	43	8000	24	PA	stainless steel	black
O-WKWG-B-M10-20-40	2	M10	40	36.5	8	43	8000	24	PA	nickel plated brass	black
O-WKWG-S-M10-20-40	2	M10	40	36.5	8	43	8000	24	PA	stainless steel	black
O-WKWG-B-M12-15-30	1.5	M12	30	27.5	6	33	5500	24	PA	nickel plated brass	black
O-WKWG-S-M12-15-30	1.5	M12	30	27.5	6	33	5500	24	PA	stainless steel	black
O-WKWG-B-M12-15-40	1.5	M12	40	37.5	8	43	8000	24	PA	nickel plated brass	black
O-WKWG-S-M12-15-40	1.5	M12	40	37.5	8	43	8000	24	PA	stainless steel	black
O-WKWG-B-M12-15-50	1.5	M12	50	47.5	10	55	9500	16	PA	nickel plated brass	black
O-WKWG-S-M12-15-50	1.5	M12	50	47.5	10	55	9500	16	PA	stainless steel	black
O-WKWG-B-M12-20-40	2	M12	40	36.5	8	43	8000	24	PA	nickel plated brass	black
O-WKWG-S-M12-20-40	2	M12	40	36.5	8	43	8000	24	PA	stainless steel	black
O-WKWG-B-M12-20-50	2	M12	50	45.5	10	55	9500	16	PA	nickel plated brass	black

Symbol	Gauge	Thread	D	D ₁	H	H ₁	Max. load static	Standard pack	Material	Insert material	Color
			[mm]	[mm]	[mm]	[mm]	[N]	[szt./pcs]			
O-WKWG-S-M12-20-50	2	M12	50	45.5	10	55	9500	16	PA	stainless steel	black
O-WKWG-B-M16-15-30	1.5	M16	30	27.5	6	33	5500	24	PA	nickel plated brass	black
O-WKWG-S-M16-15-30	1.5	M16	30	27.5	6	33	5500	24	PA	stainless steel	black
O-WKWG-B-M16-15-40	1.5	M16	40	37.5	8	43	8000	24	PA	nickel plated brass	black
O-WKWG-S-M16-15-40	1.5	M16	40	37.5	8	43	8000	24	PA	stainless steel	black
O-WKWG-B-M16-15-50	1.5	M16	50	47.5	10	55	9500	16	PA	nickel plated brass	black
O-WKWG-S-M16-15-50	1.5	M16	50	47.5	10	55	9500	16	PA	stainless steel	black
O-WKWG-B-M16-20-40	2	M16	40	36.5	8	43	8000	24	PA	nickel plated brass	black
O-WKWG-S-M16-20-40	2	M16	40	36.5	8	43	8000	24	PA	stainless steel	black
O-WKWG-B-M16-20-50	2	M16	50	45.5	10	55	9500	16	PA	nickel plated brass	black
O-WKWG-S-M16-20-50	2	M16	50	45.5	10	55	9500	16	PA	stainless steel	black
O-WKWG-B-M20-15-40	1.5	M20	40	37.5	8	43	8000	24	PA	nickel plated brass	black
O-WKWG-S-M20-15-40	1.5	M20	40	37.5	8	43	8000	24	PA	stainless steel	black
O-WKWG-B-M20-15-50	1.5	M20	50	47.5	10	55	9500	16	PA	nickel plated brass	black
O-WKWG-S-M20-15-50	1.5	M20	50	47.5	10	55	9500	16	PA	stainless steel	black
O-WKWG-B-M20-20-40	2	M20	40	36.5	8	43	8000	24	PA	nickel plated brass	black
O-WKWG-S-M20-20-40	2	M20	40	36.5	8	43	8000	24	PA	stainless steel	black
O-WKWG-B-M20-20-50	2	M20	50	45.5	10	55	9500	16	PA	nickel plated brass	black
O-WKWG-S-M20-20-50	2	M20	50	45.5	10	55	9500	16	PA	stainless steel	black