

RG - Rubber Edge Grommet



Details:

- **Material: UL-94 V-2 Nylon 6/6 RMS-01***
- **Colour: natural (NAT), black (BLK), red (RD), yellow (YL), green (GN), blue (BL)**

Symbol	Breaking force	Max. cable bundle diameter	Length L	Width W	Thickness T	Standard pack	Material	Flammability	Color
	[daN]								
RG-201	6	15	75	2.2	0.8	1000	PA 66	UL94 V-2	natural
RG-301	6	15	75	2.2	0.8	1000	PA 66	UL94 V-2	black
RG-203	8	21	98	2.5	1	1000	PA 66	UL94 V-2	natural
RG-203-BL	8	21	98	2.5	1	100	PA 66	UL94 V-2	blue
RG-203-GN	8	21	98	2.5	1	100	PA 66	UL94 V-2	green
RG-203-RD	8	21	98	2.5	1	100	PA 66	UL94 V-2	red
RG-203-YL	8	21	98	2.5	1	100	PA 66	UL94 V-2	yellow
RG-303	8	21	98	2.5	1	1000	PA 66	UL94 V-2	black
RG-205	8	32	135	2.5	1	1000	PA 66	UL94 V-2	natural
RG-305	8	32	135	2.5	1	1000	PA 66	UL94 V-2	black
RG-206	8	40	160	2.6	1.1	1000	PA 66	UL94 V-2	natural
RG-306	8	40	160	2.6	1.1	1000	PA 66	UL94 V-2	black
RG-207	8	52	200	2.6	1.1	1000	PA 66	UL94 V-2	natural
RG-307	8	52	200	2.6	1.1	1000	PA 66	UL94 V-2	black
RG-208	8	103	370	3.6	1.5	100	PA 66	UL94 V-2	natural
RG-308	8	103	370	3.6	1.5	100	PA 66	UL94 V-2	black
RG-209	13	35	140	3.6	1.1	1000	PA 66	UL94 V-2	natural
RG-209-BL	13	35	140	3.6	1.1	100	PA 66	UL94 V-2	blue
RG-209-GN	13	35	140	3.6	1.1	100	PA 66	UL94 V-2	green
RG-209-RD	13	35	140	3.6	1.1	100	PA 66	UL94 V-2	red
RG-209-YL	13	35	140	3.6	1.1	100	PA 66	UL94 V-2	yellow
RG-309	13	35	140	3.6	1.1	1000	PA 66	UL94 V-2	black
RG-214	13	50	200	3.6	1.3	1000	PA 66	UL94 V-2	natural
RG-214-BL	13	50	200	3.6	1.3	100	PA 66	UL94 V-2	blue
RG-214-GN	13	50	200	3.6	1.3	100	PA 66	UL94 V-2	green
RG-214-RD	13	50	200	3.6	1.3	100	PA 66	UL94 V-2	red

Symbol	Breaking force	Max. cable bundle diameter	Length L	Width W	Thickness T	Standard pack	Material	Flammability	Color
	[daN]	[mm]	[m]	[mm]	[mm]	[szt./pcs]			
RG-214-YL	13	50	200	3.6	1.3	100	PA 66	UL94 V-2	yellow
RG-314	13	50	200	3.6	1.3	1000	PA 66	UL94 V-2	black
RG-210	13	80	290	3.6	1.3	500	PA 66	UL94 V-2	natural
RG-310	13	80	290	3.6	1.3	500	PA 66	UL94 V-2	black
RG-212	22.4	24	120	4.5	1.4	1000	PA 66	UL94 V-2	natural
RG-312	22.4	24	120	4.5	1.4	1000	PA 66	UL94 V-2	black
RG-211	22.4	40	160	4.5	1.3	1000	PA 66	UL94 V-2	natural
RG-311	22.4	40	160	4.5	1.3	1000	PA 66	UL94 V-2	black
RG-213	22.4	45	178	4.8	1.4	1000	PA 66	UL94 V-2	natural
RG-313	22.4	45	178	4.8	1.4	1000	PA 66	UL94 V-2	black
RG-215	22.4	50	200	4.8	1.5	1000	PA 66	UL94 V-2	natural
RG-215-BL	22.4	50	200	4.8	1.3	100	PA 66	UL94 V-2	blue
RG-215-GN	22.4	50	200	4.8	1.3	100	PA 66	UL94 V-2	green
RG-215-RD	22.4	50	200	4.8	1.3	100	PA 66	UL94 V-2	red
RG-215-YL	22.4	50	200	4.8	1.3	100	PA 66	UL94 V-2	yellow
RG-315	22.4	50	200	4.8	1.5	1000	PA 66	UL94 V-2	black
RG-216	22.4	68	250	4.8	1.5	100	PA 66	UL94 V-2	natural
RG-316C	22.4	68	250	4.8	1.5	100	PA 66	UL94 V-2	black
RG-217	22.4	79	290	4.8	1.5	100	PA 66	UL94 V-2	natural
RG-217-BL	22.4	79	290	4.8	1.4	100	PA 66	UL94 V-2	blue
RG-217-GN	22.4	79	290	4.8	1.4	100	PA 66	UL94 V-2	green
RG-217-RD	22.4	79	290	4.8	1.4	100	PA 66	UL94 V-2	red
RG-217-YL	22.4	79	290	4.8	1.4	100	PA 66	UL94 V-2	yellow
RG-317	22.4	79	290	4.8	1.5	100	PA 66	UL94 V-2	black
RG-219C	22.4	103	360	4.8	1.7	100	PA 66	UL94 V-2	natural
RG-319	22.4	103	360	4.8	1.7	100	PA 66	UL94 V-2	black
RG-218	22.4	106	390	4.8	1.7	100	PA 66	UL94 V-2	natural
RG-318	22.4	106	390	4.8	1.7	100	PA 66	UL94 V-2	black
RG-220	22.4	115	430	4.8	1.7	100	PA 66	UL94 V-2	natural
RG-320	22.4	115	430	4.8	1.7	100	PA 66	UL94 V-2	black
RG-221	55	25	120	7.8	1.7	100	PA 66	UL94 V-2	natural
RG-321	55	25	120	7.8	1.7	100	PA 66	UL94 V-2	black
RG-223	55	45	180	7.8	1.7	100	PA 66	UL94 V-2	natural
RG-322	55	45	180	7.8	1.7	100	PA 66	UL94 V-2	black
RG-225	55	63	240	7.8	1.7	100	PA 66	UL94 V-2	natural
RG-325	55	63	240	7.8	1.7	100	PA 66	UL94 V-2	black
RG-226	55	80	300	7.8	1.7	100	PA 66	UL94 V-2	natural
RG-326	55	80	300	7.8	1.7	100	PA 66	UL94 V-2	black
RG-227C	55	100	365	7.5	1.7	100	PA 66	UL94 V-2	natural
RG-327	55	100	365	7.5	1.7	100	PA 66	UL94 V-2	black
RG-229	55	130	450	7.5	1.7	100	PA 66	UL94 V-2	natural
RG-329	55	130	450	7.5	1.7	100	PA 66	UL94 V-2	black
RG-231	55	158	540	7.5	1.7	100	PA 66	UL94 V-2	natural
RG-331	55	158	540	7.5	1.7	100	PA 66	UL94 V-2	black
RG-233	55	220	750	7.8	1.7	100	PA 66	UL94 V-2	natural
RG-333	55	220	750	7.8	1.7	100	PA 66	UL94 V-2	black
RG-234	71	233	780	9	2	100	PA 66	UL94 V-2	natural
RG-334	71	233	780	9	2	100	PA 66	UL94 V-2	black
RG-235	110	57	225	12.5	2	50	PA 66	UL94 V-2	natural
RG-335	110	57	225	12.5	2	50	PA 66	UL94 V-2	black
RG-237	110	143	500	12.5	2	50	PA 66	UL94 V-2	natural
RG-337	110	143	500	12.5	2	50	PA 66	UL94 V-2	black
RG-239	110	213	720	12.5	2	50	PA 66	UL94 V-2	natural
RG-339	110	213	720	12.5	2	50	PA 66	UL94 V-2	black

Symbol	Breaking force	Max. cable bundle diameter	Length L	Width W	Thickness T	Standard pack	Material	Flammability	Color
	[daN]	[mm]	[m]	[mm]	[mm]	[szt./pcs]			
RG-241	110	255	850	12.5	2	50	PA 66	UL94 V-2	natural
RG-341	110	255	850	12.5	2	50	PA 66	UL94 V-2	black
RG-243	110	302	1000	12.5	2	50	PA 66	UL94 V-2	natural
RG-343	110	302	1000	12.5	2	50	PA 66	UL94 V-2	black