**IP Kontakt**
Pl. Zwycięstwa 2E
90-312 Łódź
Poland
tel. +48 42 676 75 25
+48 42 674 22 74
+48 42 674 22 88
e-mail: *ipkontakt@ipkontakt.pl*

# DTS-T-446 - Double-Sided Adhesive Tapes with Cloth Carrier



Details:

- **DTS-446** is high-quality double-sided cloth installation tape for professional requirements.
- The covered side of the tape is coated with a permanent acrylic adhesive, while the removable adhesive on the open side can be removed from almost a
  ll surfaces without leaving any residue
- **DTS-446** is solvent-free and has a good resistance to aging and plasticizers
- Shear Adhesion (25 mm² on V2A steel, 1 kg weight at 23° and 50 % rel. atmospheric humidity): >1 h
- The prohibited substances according to the RoHS directive (2002/95/EC) and 2006/122/EG (PFOS) are not included in this product
- Storage: Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of one year
- Application: Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

| Symbol | Adhesive | Carrier | Thickness [mm] | Liner | Peel 180° [N/25mm] | Temperature [°C] |
|---|---|---|---|---|---|---|
| DTS-T-446-R | Acrylic, removable | fabric | 0.32 | Paper, white | > 3 | -20 to +100 |