


IP Kontakt Pl. Zwycięstwa 2E 90-312 Łódź tel. +48 42 676 75 25 +48 42 674 22 74 +48 42 674 22 88

Poland e-mail: ipkontakt@ipkontakt.pl

H-PPL -





Details:

- Material: Nylon 6/6
- Flammability Rating: UL94 V-2
- Colour: black and natural
- Temperature Range: 0°C to 85°C
- Flexible and tapered prongs on plug will snugly lock in place with fingertip pressure, but can be removed & reused.
- Durable and non-conductive.
- $\bullet\,$ Excellent dust protection for electronic equipment.
- Abrasion and vibration resistant.
- May be used as temporary or permanent hole plugs.
- Function as feet on small appliances.
- May be used to close tube ends.

| Symbol | Mounting hole diameter range | Panel thickness range | Head diameter ØA | В | Material | Flammability | Color | Uwagi / Notes |
|---------|------------------------------|-----------------------|---------------------|------|----------|--------------|---------|---------------|
| | [mm] | [mm] | [mm] | [mm] | | | | |
| H-12183 | 9.5 - 9.7 | 2.4 - 7.9 | 12.4 | 13.5 | PA 66 | UL94 V-2 | natural | glossy head |

ipkontakt.pl Page 1 of 1