IP Kontakt
Pl. Zwycięstwa 2E
90-312 Łódź
Poland
tel. +48 42 676 75 25
+48 42 674 22 74
+48 42 674 22 88
e-mail: *ipkontakt@ipkontakt.pl*

H-EXR - Expansion rivets



Typ 1
Type 1



Typ 2
Type 2

Details:

- **Type 1:**
  - **Body material: Nylon 6/6**
  - **Pin material: Acetal (POM)**
  - Body flammability: UL94 V-2
  - Pin flammability: UL94 HB
- **Type 2:**
  - **Body material: Nylon 6/6**
  - **Pin material: polycarbonate**
  - Body and pin flammability: UL94 V-2
- Colour: black
- Temperature Range: -40°C to 120°C
- One-piece, all plastic expansion rivet.
- Designed to securely fasten a wide variety of materials in a range of applications.
- Inserts quickly from either side of assembly.
- Use with standard rivet setting tool - pull the pin through the body and panels are drawn together.
- Pin breaks off even with head and leaves an attractive, finished appearance.
- Effective for soft materials such as rubber, padded fabrics, etc.

Symbol	Mounting hole diameter	Panel thickness range	A	Head height B	Head diameter C	Type	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]	[mm]				
H-12661	5.7	8.0 - 11.5	15.9	2.2	12	2	PA 66 + PC	UL94 V-2	black