

## H-LTTVP - Liquid Tight Threaded Vent Plugs



**Zintegrowana  
uszczelka**  
*Integral sealing  
ring*



### Details:

- **Material:**
  - **Body:** Nylon 6/6
  - **Filter:** Acrylic Copolymer
- **Flammability rating:** UL94 V-2
- **IP rating:** IP 65/66/68
- **IP rating for NPT 3/4" thread:** IP 65
- **Colour:** black, szary
- Temperature range: -40°C to 105°C
- Allow the passage of air for ventilation and heat dissipation, yet prevent moisture intrusion, remain liquid tight.
- Maximum airflow:  $\geq 16.6 \text{ LPM}/3.7\text{cm}^2$  @ 13.5 psi.
- Pressure compensating seal prevents buildup of pressure inside of electronic enclosures due to environmental temperature cycling.
- Approximate Head Thickness: 5.3 mm. Thickness may vary.

| Symbol   | Ext. thread | Wrench size<br>A | Height<br>B | Material | Flammability | Color |
|----------|-------------|------------------|-------------|----------|--------------|-------|
|          |             | [mm]             | [mm]        |          |              |       |
| H-3544VB | NPT 1/4     | 16               | 16.8        | PA 66    | UL94 V-2     | black |