





**H-DC -**





**H-4240, H-4250**




**Otwór montażowy**  
*Mounting hole*



**H-4380**




**Otwór montażowy**  
*Mounting hole*




**H-4440**


Ø19.8




**D**



8.4




**Otwór montażowy**  
*Mounting hole*




**H-4428**


Ø19.8




**D**



8.4




**Otwór montażowy**  
*Mounting hole*





**H-4270**


Ø14






**D**




**Otwór montażowy**  
*Mounting hole*






**H-4410**




**Otwór montażowy**  
*Mounting hole*






**H-4470**



**Otwór montażowy**  
*Mounting hole*



**H-4468**



**Otwór montażowy**  
*Mounting hole*

Details:

- **Material: Polycarbonate UL94 V-0**
- **Colour: black, other colours available on special order**
- Certifications Recognized under the Component Program of Underwriters' Laboratories File E467283 to both Canadian and US Requirements Flammability
- Temperature Range: 32°C to 130°C
- Small, snap-in nylon receptacles for low cost, insulated, quick connection or disconnection of your wires, through panels, housings or detachable shrouds.
- Typical uses are data processing and vending machines, motors, power supplies, and controls.
- H-4240, H-4250, H-4380, H-4440, H-4428 - Bushings with Double Male Terminals
- H-4270, H-4410, H-4470, H-4468 - Bushings with Tinned Male to Solder Terminals

Symbol	Polarized	Number of poles	Terminal width	A	B	C	D	Material	Flammability	Color
			[mm]	[mm]	[mm]	[mm]				
H-4240	no	1	6.4	12.7	11.8	3.2	23.9	PC	UL94 V-0	black