

IP Kontakt
Pl. Zwycięstwa 2E
90-312 Łódź
Poland
tel. +48 42 676 75 25
+48 42 674 22 74
+48 42 674 22 88
e-mail: *ipkontakt@ipkontakt.pl*

H-SCG - Snap-In Cordgrip Strain Reliefs





Sugerowany otwór przelotowy do montażu zatrzaskowego
Suggested clearance hole for snap-in mounting



Details:

- **Material: Nylon 6/6**
- **Flammability Rating: UL94 V-2**
- **Temperature Range: -18°C to 105°C**
- **Panel thickness: 1.6 mm - 3.2 mm**
- **Colour: BLK - black, GR - grey**
- Unique fingers securely lock into a range of panel sizes without use of locknut.
- Smooth, rounded interior edges for ease of installation.
- Limited intrusion into enclosure where access is tight.
- Rotation prevented when used in Double D mounting holes.
- Easy to install–no tools required.
- Ratchet design of sealing nut assembly provides superior antivibration and ensures a firm grip on the cable.

Symbol	Cable diameter range	Mounting hole dimentions A × B	C	Panel thickness range	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]			
H-M4837	11.0 - 17.9	28.6 × 25.4	44.5	1.6 - 3.2	PA 66	UL94 V-2	grey