

LCBS - Locking Circuit Board Support

LCBS

Top Hole: Snap-lock: 4 ± 0.08
 Panel Thickness: 1.57

Fig. 1




Bottom Hole: Snap-lock: 4.75 ± 0.08
 Panel Thickness: 0.79 - 1.98

LCBS-2

Top Hole: Snap-lock: 4 ± 0.08
 Panel Thickness: 1.57

Fig. 2




Bottom Hole: Snap-lock: 4.75 ± 0.08
 Panel Thickness: 1.98 - 3.58

LCBS-3

Top Hole: Snap-lock: 4 ± 0.08
 Panel Thickness: 2.4

Fig. 3




Bottom Hole: Snap-lock: 4.75 ± 0.08
 Panel Thickness: 0.79 - 1.98

LCBS-4

Top Hole: Snap-fit: $\varnothing 4 \pm 0.08$
 Panel Thickness: 1.57

Fig. 4




Bottom Hole: Snap-lock: $\varnothing 4.75 \pm 0.08$
 Panel Thickness: 0.79 - 1.98



LCBS-5

Top Hole: Snap-lock: $\varnothing 4 \pm 0.08$
 Panel Thickness: 1.6

Fig. 5




Bottom Hole: Snap-lock: $\varnothing 4.8 \pm 0.08$
 Panel Thickness: 0.76 - 2

LCBS-6

Top Hole: Snap-lock: $\varnothing 4$
 Panel Thickness: 3.2

Fig. 6




Bottom Hole: $\varnothing 4.8$
 Panel Thickness: 2 - 3.2

LCBS-7

Top Hole: Snap-lock: $\varnothing 4 \pm 0.08$
 Panel Thickness: 1.6

Fig. 7




Bottom Hole Snap-lock: $\varnothing 4.75 \pm 0.08$
 Panel Thickness: 0.8 - 2

LCBS-8

Top Hole: Snap-lock: 4 ± 0.08
 Panel Thickness: 1.57

Fig. 8



Bottom Hole: Snap-lock: 4.75 ± 0.08
 Panel Thickness: 0.2 - 1.4

Details:

- **Material and color: see table**
- **Standard pack: 1000 pcs.**

Symbol	Height A	Top mounting hole dia. ± 0.08	Top panel thickness	Bottom mounting hole dia. ± 0.08	Bottom panel thickness range	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]	[mm]			
LCBS-8-18-19	28.6	4	1.57	4.75	0.2 - 1.4	PA 66	UL94 V-0	natural