

## OR-DL-WM-M - Metal cable glands, ventilated, metric thread



### Details:

- **Body material:** brass with/without nickel plated / AISI303/316L Stainless Steel
- **Plastic part:** PA6 V2 / V0
- **Sealing:** TPV / Silicone
- **O-ring:** NBR / EPDM / Silicone
- **Vent part:** Acrylic Co-Polymer on Nylon Support (Hydrophobic-Oleophobic)
- **Protection class:** IP68
- **Temperature Range:** -40 °C +105 °C
- Prevents the pressure inside the device to increase
- Prevents heat rise by providing air circulation
- Minimizes or even eliminates negative effects due to humidity in the environment
- Minimizes periodic cleaning costs by eliminating condensation and evaporation problems due to relative humidity in LED fittings and connection boxes
- Extends the life of the device

| Symbol            | Metric thread | H    | Thread length<br>GL | Wrench size<br>SW | Mounting hole<br>diameter | Cable diameter range | Material        |
|-------------------|---------------|------|---------------------|-------------------|---------------------------|----------------------|-----------------|
|                   |               | [mm] | [mm]                | [mm]              | [mm]                      | [mm]                 |                 |
| OR-DL-WMS-M20x1.5 | M20x1.5       | 35   | 8                   | 22                | 20.3                      | 6 - 12               | stainless steel |