

## OR-DL-WP-M - Plastic cable glands, ventilated, metric



### Details:

- **Body material: PA6**
- **Membrane material: Hydrophobic - Oleophobic**
- **O-ring material: NBR / EPDM**
- **Gasket material: thermoplastic vulcanized TPV**
- **Colour: RAL 7001 (Gray), RAL 7035 (Light Gray) or RAL 9005 (Black)**
- Thread: metric EN 60423
- Protection: IP68
- Continuous heat resistance: -30°C to +80°C
- Short term heat resistance: +150 ° C
- Prevents the pressure inside the device to increase
- Prevents heat rise by providing air circulation
- Minimizes or even eliminates negative effects due to humidity in the environment
- Minimizes periodic cleaning costs by eliminating condensation and evaporation problems due to relative humidity in LED fittings and connection boxes
- Extends the life of the device
- Average air flow: 70 l/h
- Water intrusion: 0.1 bar

| Symbol               | Metric thread<br>AG | H    | Thread<br>length<br>GL | Wrench size | Cable diameter<br>range | Mounting hole<br>diameter | Material | Color      |
|----------------------|---------------------|------|------------------------|-------------|-------------------------|---------------------------|----------|------------|
|                      |                     | [mm] | [mm]                   |             |                         |                           |          |            |
| OR-DL-WP-M20X1.5-LGR | M20×1.5             | 40.5 | 10                     | 24          | 4 - 10                  | 20.3                      | PA 6     | light grey |