

IP Kontakt
Pl. Zwycięstwa 2E
90-312 Łódź
Poland
tel. +48 42 676 75 25
+48 42 674 22 74
+48 42 674 22 88
e-mail: *ipkontakt@ipkontakt.pl*

WL-LH - Adhesive cable holders







Details:

- **Material: PA 6.6/6 + adhesive tape**
- **Colour: natural or black (more resistant to UV)**
- Raw material flammability UL94 V-2
- Humidity absorption: 2,7% - 2,8% (23°C - 50% R.H.)
- Installation temperature (with adhesive): -10°C to +85°C
- Installation temperature (without adhesive): -25°C to +85°C
- Working temperature: -40°C to +85°C
- Good resistance to bases, oils, greases, oil derivates, chloride solvents. Limited resistance to acids. Not resistant to phenols.
- It is recommended that adhesive mounts to be sticked 2 hours prior to loading. Adhesive tape is the best choice for most adhesive mount applications, including powder coated surfaces.

Symbol	A	B	C	D	E	Max. cable bundle diameter	Material	Flammability	Color
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]			
WL-LH-12-3/4-BLK	15.4	17.1	18.1	25	25	16	PA 66	UL94 V-2	black