



IP Kontakt
Pl. Zwycięstwa 2E
90-312 Łódź
Polska
tel. +48 42 676 75 25
+48 42 674 22 74
+48 42 674 22 88
e-mail: *ipkontakt@ipkontakt.pl*

DLCBS - Tulejka dystansowa nylonowa


DLCBS Fig. 1
Top Hole: Snap-lock: 4 ± 0.08
Panel Thickness: 0.79 - 1.98

Bottom Hole: Snap-lock: 4 ± 0.08
Panel Thickness: 0.79 - 1.98


DLCBS2 Fig. 2
Top Hole: Snap-lock: 4.75 ± 0.08
Panel Thickness: 0.79 - 1.98

Bottom Hole: Snap-lock: 4.75 ± 0.08
Panel Thickness: 0.79 - 1.98


DLCBS3 Fig. 3
Top Hole: Snap-lock: 4 ± 0.08
Panel Thickness: 0.79 - 1.98

Bottom Hole: Snap-lock: 4.75 ± 0.08
Panel Thickness: 0.79 - 1.98


DLCBS6 Fig. 4
Top Hole: Snap-Lock Ø 3.5 ±0.08
Panel Thickness: 0.8-2

Bottom Hole: Snap-Lock Ø 3.5 ±0.08
Panel Thickness: 0.8-2



DLCBS6 Fig. 5
Top Hole: Snap-Lock Ø 4.75 ±0.08
Panel Thickness: 0.8-2

Bottom Hole: Snap-Lock Ø 3.5 ±0.08
Panel Thickness: 0.8-2

DLCBS7 Fig. 6
Top Hole: Snap-Lock Ø4 ±0.08
Panel Thickness: 1.6

Bottom Hole: Snap-Lock Ø4 ±0.08
Panel Thickness: 1.6

DLCBS8 Fig. 7
Top Hole: Snap-Lock Ø3.5 ±0.08
Panel Thickness: 0.8-1.6

Bottom Hole: Snap-Lock Ø3.5 ±0.08
Panel Thickness: 0.8-2

DLCBSM Fig. 8
Top Hole: Snap-lock: 3.18 ± 0.05
Panel Thickness: 0.79 - 1.98

Bottom Hole: Snap-lock: 3.18 ± 0.05
Panel Thickness: 0.79 - 1.98

Dane techniczne:

- **Nylon 6/6, UL 94 V-2, RMS-01 ***
- **Nylon 6/6, UL 94 V-0, RMS-19 ***
- **Kolor:** naturalny
- Minimum zakupu: 1000 szt.

Symbol	Wysokość A	Średn. otworu górnego ±0.08	Zakres grubości panelu górnego	Średn. otworu dolnego ±0.08	Zakres grubości panelu dolnego	Materiał	Klasa palności	Kolor
	[mm]	[mm]	[mm]	[mm]	[mm]			
DLCBS5-3-01	4.8	3.5	0.8 - 2	3.5	0.8 - 2	PA 66	UL94 V-2	naturalny