

H-PRT - Żebrowane wkładki do rur okrągłych



Dane techniczne:

- **Materiał:** LDPE
- **Kolor:** czarny
- Zakres temperatur: -70°C do 66°C

Symbol	Średnica wkładki A	B	Średnica wewnętrzna rury	Moduł	Materiał	Kolor
	[mm]		[mm]			
H-G5220	12.7	11.4	7.9 - 8.4	13 - 14	LDPE	czarny
H-G5221	12.7	11.4	9.4 - 10.9	16 - 20	LDPE	czarny
H-G5223	15.9	11.2	11.7 - 14.2	14 - 20	LDPE	czarny
H-G5224	19.1	11.2	14.7 - 17.3	14 - 20	LDPE	czarny
H-G5225	22.2	11.2	15.5 - 18.1	10 - 14	LDPE	czarny
H-G5226	22.2	11.2	18 - 23.1	14 - 20	LDPE	czarny
H-G5227	25.4	11.2	18.5 - 21.1	10 - 14	LDPE	czarny
H-G5228	25.4	11.2	21 - 23.6	14 - 20	LDPE	czarny
H-G5229	28.6	13.2	23.4 - 26.9	14 - 20	LDPE	czarny
H-G5230	31.8	13.2	24.9 - 27.4	10 - 14	LDPE	czarny
H-G5231	31.8	13.2	27.4 - 30	14 - 20	LDPE	czarny
H-G5232	34.9	12.7	30.7 - 33.3	14 - 20	LDPE	czarny
H-G5233	38.1	13.2	29.7 - 32.5	8 - 12	LDPE	czarny
H-G5234	38.1	13.2	21.2 - 33.8	10 - 14	LDPE	czarny
H-G5235	38.1	13.2	33.8 - 36.3	14 - 20	LDPE	czarny
H-G5236	41.3	12.7	34.5 - 37.1	10 - 14	LDPE	czarny
H-G5237	41.3	13.2	37 - 39.6	14 - 20	LDPE	czarny
H-G5238	44.5	15	37.6 - 40.1	10 - 14	LDPE	czarny
H-G5239	44.5	15	40.1 - 42.7	14 - 20	LDPE	czarny
H-G5241	49.5	15	43.9 - 46.5	10 - 14	LDPE	czarny
H-G5242	50.8	15	46.5 - 49	14 - 20	LDPE	czarny
H-G5243	54	17	47.2 - 50.8	10 - 14	LDPE	czarny
H-G5244	57.2	16.8	50.3 - 52.8	10 - 14	LDPE	czarny
H-G5245	57.2	17.5	52.8 - 53.4	14 - 20	LDPE	czarny

Symbol	Średnica wkładki A	B	Średnica wewnętrzna rury	Moduł	Materiał	Kolor
	[mm]	[mm]	[mm]			
H-G5246	60.3	16.8	53.6 - 56.1	10 - 14	LDPE	czarny
H-G5247	63.5	17.5	55.1 - 57.9	8 - 12	LDPE	czarny
H-G5248	63.5	17.5	61.7 - 62.7	14 - 20	LDPE	czarny